世界知的所有権機関

PCT

国際事務局



特許協力条約に基づいて公開された国際出願

			(11)	国際公開番号	WO 95/03603
G11B 5/66, 5/8	34, <i>5</i> /85	Al	•		
			(43)	国際公開日	~短、 1995年2月2日 (02.02.1995)
(21) 国際出願番号 (22) 国際出願日	POT/J 1994年7月19日(P94/01:			
	1993年7月21日(21. 07. 93) 1994年1月24日(24. 01. 94)	JP JP			
(71) 出願人; および (72) 発明者 高格 研(TAKAHASHI	.Migaku)(JP∕JP)				
〒980 宮城県仙台市太白 (74) 代理人 弁理士 福森久夫(FUKU) 〒160 東京都新宿区本塩	•	, (JP)			
(74) 代理人 弁建士 福森久夫(FUKU) 〒160 東京都新宿区本場 (81) 指定国 CN, JP, KR, US, E	MORI, Hisao)	DK, ES	,		
(74) 代理人 弁建士 福森久夫(FUKU) 〒160 東京都新宿区本場 (81) 指定国 CN, JP, KR, US, E	MORI, Hisao) 町12 Tokyo, (JP) 欧州特許(AT, BE, OH, DE, IT, LU, MO, NL, PT, SB	DK, ES			
(74) 代理人 弁理士 福森久夫(FUKU) 〒160 東京都新宿区本地 (81) 指定国 CN, JP, KR, US, E FR, GB, GR, IE,	MORI, Hisao) 町12 Tokyo, (JP) 欧州特許(AT, BE, OH, DE, IT, LU, MO, NL, PT, SB	DK, ES			

(54) 発明の名称 磁気配象媒体及びその製造方法

(57) Abstract

An inexpensive high-density recording medium which is increased in coercive force without using expensive ferromagnetic metallic layer. In a magnetic recording medium on the substrate of which a ferromagnetic metallic layer is formed on a substrate with a metallic underlying layer in between and which utilizes reversal of magnetization, the oxygen concentration in the ferromagnetic metallic layer is below 100 wt. ppm, and in addition, the oxygen concentration in the metallic base layer is also below 100 wt. ppm. In a method of manufacturing a magnetic recording medium on the substrate of which the metallic base layer and ferromagnetic metallic layer are successively formed by sputtering, the impurity concentration of Ar gas used for the formation of the layers is below 10 ppb. Before forming the metallic base layer, in addition, the surface of the substrate is cleaned by high-frequency sputtering using Ar gas the impurity concentration of which is 10 ppb and the surface section of the substrate is partially removed to a depthof 0.2-1 nm.

